

T5

For excavators 4.0-6.0 ton



MZ



HF2
Ø max 5 cm
**STANDARD
EQUIPMENT**



HC1
Ø max 4 cm



KC1
Ø max 3 cm

T5

	ton	4.0-6.0
	cm/inch	105 42
	cm/inch	130x60x40 52-24-16
	kg/lbs	190 419
	cc	16
	oil - L/min (gal/min)	40-11
	bar/psi (min-max)	170-220 2.500-3.200
	transmission	direct
	rotor diameter cm/inch	38 15
		16

Technical features and standard equipment

- Direct transmission
- Internally reinforced with double metal sheet
- Feeler roller adjustable on 3 positions to change the height of the cut
- Helicoidal rotor with austempered hammers or blade interchangeable
- Protective cover for motor
- Inside rotor supports with labyrinth for the protection of the bearings from the impurities
- Double row spherical adjustable bearings of 1st quality
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation
- Gear motor
- Accident prevention rubber protections according to EC directives

Accessories

- Mounting hitch (pins version)
- Pins kit
- Quick hitch
- Hoses kit Lg. 2 meters
- Front chain protection
- Self-levelling support (+40kg)
- Valves block deduction, only anticavitation
- Cast iron gear motor group 3 instead of group 2

Hydraulic motor range

	ton	4-6
	CC	16
	oil - L/min gal/min	40 11

Cast iron hydraulic gear motor range

	ton	6-7	7-8	8-9
	CC	22	27	34
	oil - L/min gal/min	60 16	70 19	80 22