



## SA1000 SWIVEL TRIM WITH MULTI-SAW

The Slanetrac SA1000 Swivel Trim with Multi-Saw is a versatile trimming solution designed for tractors, skid steers, and telehandlers. It delivers efficient and controlled cutting across a wide range of applications. Powered by the carrier's hydraulics, it provides smooth, consistent saw performance with simple hydraulic adjustment from horizontal to vertical cutting angles.

Ideal for fruit tree pruning across tropical varieties such as custard apple, lychee, mango, and macadamia, as well as citrus, apple, and olive trees. This setup also excels in coarse hedge trimming, nursery work for saplings and young plants, and roadside vegetation management.

The high RPM saw heads produce clean cuts and reliable output throughout long working days. Built for productivity, it is a practical solution for professional orchard, agricultural, and municipal operations.

### STANDARD FEATURES:

- Horizontal Reach: Manually telescopes out to 1,000 mm
- 180 Swivel: Swing cutting head to opposite side of machine
- Hydraulic Cutting Head Angle Adjustment: 110°
- Spring Breakaway – Protects cutting head from damage
- Spline Mount for interchangeable cutting heads





Model	Rinieri Triple Saw (6TDL100)	Rinieri Quad Saw (6TDL140)	Rinieri Six Saw (6TDL200)
Cutting Width	1000 mm	1400 mm	2000 mm
Cutting Diameter	80 mm	80 mm	80 mm
Weight (including SA1000)	335 kg	340 kg	360 kg
Saw Blades	3 x 400 mm (individually replaceable)	4 x 400 mm (individually replaceable)	6 x 400 mm (individually replaceable)
Oil Flow Required	45 L/min	45 L/min	50 L/min
Gear Motor	Casappa Cast Iron	Casappa Cast Iron	Casappa Cast Iron
Drive System	Belt Drive	Belt Drive	Belt Drive
Recommended Carrier	Tractor from 60 hp	Tractor from 60 hp	Tractor from 60 hp

#### Hitch Options:

- **Euro hitch** (standard)
- **Universal skid steer hitch** (includes 12v solenoid for machines without auxiliary hydraulic circuit)
- **Telehandler hitch**
- **Challenge/Aus hitch**
- **Blank hitch** – with plates to suit welding custom mount



*Also available with 1500 mm, 1800 mm, 2500 mm, and 3000 mm cutter bars.*